



Extra Comfort and Functionality

Scissor Lift

Series PTH50 S / PS



PTH50 PS
Electro hydraulic
system



PTH50 S
Manual hydraulic
system

With many options as either a hand pallet lift truck, storage table or workbench, the truck saves the operator a lot of work, avoiding unnecessary bending and heavy lifting.

Manual hydraulic system

The scissor lift trucks can be moved to a lift height of up to 400 mm, at which point they automatically disengage the steer wheels.

- Hydraulic system with overload valve
- Top of stroke bypass to protect the hydraulic system
- Hard-chrome piston rod
- Smooth and quiet wheels

Electro hydraulic system

Fast and quiet height adjustment at the press of a button, for applications requiring frequently varied working heights. Standard features as for the manual hydraulic version with the following additions:

- Solid metal covers
- Maintenance-free battery, cycle and vibration safe, 12 volt / 60 Ah
- Discharge indicator with lift cut-out to prevent full discharge
- On-board charger, 12 volt / 10 Amps
- All manual lifting and lowering functions are retained

Technical data's

Scissorlift	PTH50 S	PTH50 PS	
Power, hydraulic	manual	manual/electric	
Load Capacity	kg	1000	
Load Center	mm	600	
Fork Length	mm	1150	
Overall Length	mm	1590	1645
Overall Width	mm	540	
Fork Width	mm	160	
Lift Height	mm	800	
Lowered Fork Height	mm	85	
Steer Angle	°	200	
Steer Wheels	mm	Poly 180 x 50	
Load Wheels (single)	mm	Poly 74 x 75	

* Supplied with battery, charger and mains cable with housing